

## HEXON ATF V (LT71141)

### DESCRIPTION

This is a premium quality, fully synthetic, multi-vehicle, low viscosity automatic transmission fluid. It contains a special blend of synthetic base fluids and a carefully balanced multifunctional additive system that provides superior friction durability, and protection against shudder, and allows the proper friction retention needed for long-life performance and smooth lockups and a highly shear stable viscosity improver.

### CARACTERISTICS

- Excellent low-temperature fluidity to ensure proper operation of today's transmissions fitted with electronic controls and smaller orifices;
- Excellent oxidation and thermal stability;
- Excellent resistance to thermal degradation;
- Outstanding resistance against sludge and deposit formation.

### APPLICATION

This special Automatic Transmission Fluid is recommended for use mostly for vehicles that require LT 71141. Also, it can be used on General Motors and Ford vehicles.

### PERFORMANCE

GM DEXRON, JASO 1-A, FORD MERCON V- CATERPILLAR TO-2, ALLISON C-4, VOLVO 97340

### TYPICAL PROPERTIES

TEST	METHOD	UNIT	TYPICAL VALUES
Density, @15 C	ASTM D 4052	g/ml	0,86
K.Viscosity @40 C	ASTM D 445	cSt	32,2
K.Viscosity @100 C	ASTM D 446	cSt	7,5
Viscosity Index	ASTMD D 2270		181
Flash Point	ASTM D 92	°C	240
Pour Point	ASTM D 97	°C	-48



\* Values shown may differ between productions

