

## HEXON HYDRAULIC ISO 32

### DESCRIPTION

This series is for hydraulic system oils, specially designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion, and anti-foam additives.

### CARACTERISTICS

- Prolongs the life of equipment by preserving the properties even under high-temperature conditions.
- Greatly protects the hydraulic system parts thanks to its superior abrasion properties.
- High thermal stability and long service life thanks to its high oxidation resistance.
- Good filterability and high resistance to foaming.
- Prevents corrosion within the system and prolongs the life of the equipment

### APPLICATION

The Hydraulic System Oil Series offer general-purpose oils used for hydraulic pump systems that run under normal operating conditions, which are produced by blending mineral oil with additives that protect against rust and corrosion.

### PERFORMANCE

- DIN 51524 PART 2, DENISION HF 0/1/2

### TYPICAL PROPERTIES

TEST	METHOD	UNIT	TYPICAL VALUES
Density, @15 °C	ASTM D 4052	g/ml	0,876
K.Viscosity @40 °C	ASTM D 445	cSt	32
K.Viscosity @100 °C	ASTM D 446	cSt	5.6
Viscosity Index	ASTMD D 2270		114
Flash Point	ASTM D 92	°C	216
Pour Point	ASTM D 97	°C	-27

\* Values shown may differ between productions

