

HEXON MULTI SYN 5W-30

DESCRIPTION

A full synthetic engine oil, designed for all modern gasoline and diesel engines that require instant lubrication from the first start. It is formulated with high-technology additives and synthetic base oils. It forms an additional lubricating film layer that adheres to mechanical parts (piston/cylinder) and protects against wear.

CARACTERISTICS

- Total engine protection and high performance in keeping the engine clean;
- Superior fuel economy.
- Cold start and excellent fluidity at low temperatures;
- Provides high engine performance by reducing friction;
- Provide protection against power loss and ensure continuity of engine functioning;
- Top-level residue and soot control.

APPLICATION

It is suitable for all LPG gasoline and diesel engines. Recommended for every season and any driving conditions.

PERFORMANCE

API SN/CF, ACEA C2/C3, MB-Approval 229,51 MB 226,51/229,31/229,52 , BMW LL-04, GM DEXOS 2, PORSCHE C30, RENAULT RN 0700 / 0710, PSA B71 2290, Ford WSS-M2C913-D, FIAT 9.55535-GH2 / S1, VW 507 00 / 505 00 / 505 01, OPEL OV0401547 – D30 / OV0401547 – G3.

TYPICAL PROPERTIES

TEST	METHOD	UNIT	TYPICAL VALUES
Density, @15 °C	ASTM D 4052	g/ml	0,850
K.Viscosity @40 °C	ASTM D 445	cSt	71,1
K.Viscosity @100 °C	ASTM D 446	cSt	12,2
Viscosity Index	ASTMD D 2270		170
Flash Point	ASTM D 92	°C	220
Pour Point	ASTM D 97	°C	-39

* Values shown may differ between productions

