

HEXON SUPER PLUS 10W-30

-HEAVY DUTY-

DESCRIPTION

Hexon 10W- 30 is a full synthetic motor oil engineered with superior performance on a wide range of engines of passenger cars, vans and light trucks.

Providing outstanding wear and sludge protection, even under the most severe driving conditions.

CHARACTERISTICS

- Excellent low-temperature properties.
- Protection against ring sticking.
- Viscosity maintenance and reduced oil consumption under heavy-duty, high-temperature operating conditions.
- Provide long engine life.

APPLICATION

Recommended for use in diesel engine oils including turbocharged and gasoline fueled vehicles.

PERFORMANCE

API SN/CF, ACEA E7/E9, MB 228.3, RENAULT RLD-3, VOLVO VDS-4.5, CAT ECF-3, CUMMINS CES 20086, DETROIT DIESEL DFS 93K222, DEUTZ DQC III-18 LA

TYPICAL PROPERTIES

TEST	METHOD	UNIT	TYPICAL VALUES
Density, @15 C	ASTM D 4052	g/ml	0,8634
K.Viscosity @40 C	ASTM D 445	cSt	71,44
K.Viscosity @100 C	ASTM D 446	cSt	10,97
Viscosity Index	ASTMD D 2270		144
Pour Point	ASTM D 97	°C	-36

* Values shown may differ between productions

